

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

1 Identification

- **Product identifier**

- **Trade name:** Sure Bond™ J58 - Part A

- **Article number:** 87-307267A

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Dayton® Superior

4226 Kansas Avenue

Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Eye Irrit. 2A H319 Causes serious eye irritation.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Warning

- **Hazard statements**

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 1

Reactivity = 0

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part A

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = 1
FIRE	1	Fire = 1
PHYSICAL HAZARD	0	Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

25085-99-8	Diglycidyl ether of bisphenol A homopolymer	75-100%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	≤ 2.5%
13463-67-7	titanium dioxide	≤ 1%
84852-15-3	4-nonylphenol, branched	≤ 1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Seek medical treatment.

· Information for doctor:

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part A

(Contd. of page 2)

- **Advice for firefighters**

- **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

13463-67-7	titanium dioxide	30 mg/m ³
84852-15-3	4-nonylphenol, branched	3.9 mg/m ³

- **PAC-2:**

13463-67-7	titanium dioxide	330 mg/m ³
84852-15-3	4-nonylphenol, branched	43 mg/m ³

- **PAC-3:**

13463-67-7	titanium dioxide	2,000 mg/m ³
84852-15-3	4-nonylphenol, branched	260 mg/m ³

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- **Information about protection against explosions and fires:** No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:** cool and dry

- **Requirements to be met by storerooms and receptacles:** Store in a cool dry location.

- **Information about storage in one common storage facility:**

Store away from incompatible materials.

Store away from foodstuffs.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part A

(Contd. of page 3)

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	Clear
- **Odor:** Mild
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
- **Flash point:** >94 °C (>201 °F)
- **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part A

(Contd. of page 4)

· Ignition temperature:	
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.164 g/cm ³ (9.714 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
Solids content:	100.0 %
· Other information	No further relevant information available.
· Volatile Organic Compounds:	Not determined

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with acids, alkalis and oxidizing agents.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

25085-99-8 Diglycidyl ether of bisphenol A homopolymer

Oral	LD50	5000 mg/kg (rat)
------	------	------------------

Dermal	LD50	20000 mg/kg (rabbit)
--------	------	----------------------

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part A

(Contd. of page 5)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**
Strong irritant with the danger of severe eye injury.
Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)	
13463-67-7 titanium dioxide	2B

· NTP (National Toxicology Program)
None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part A

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADR, ADN, IATA · IMDG 	<p style="text-align: right;">Not Regulated UN3082</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT, ADR, ADN, IATA · IMDG 	<p style="text-align: right;">Not Regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin, zinc oxide), MARINE POLLUTANT</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT, ADR, ADN, IATA · Class 	<p style="text-align: right;">Not Regulated</p>
<ul style="list-style-type: none"> · IMDG <div style="text-align: center;">  </div>	<p style="text-align: right;">9 Miscellaneous dangerous substances and articles 9</p>
<ul style="list-style-type: none"> · Class · Label 	<p style="text-align: right;">9 Miscellaneous dangerous substances and articles 9</p>
<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	<p style="text-align: right;">III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p style="text-align: right;">Product contains environmentally hazardous substances: zinc oxide Yes Symbol (fish and tree)</p>
<ul style="list-style-type: none"> · Special precautions for user · EMS Number: · Stowage Category 	<p style="text-align: right;">F-A,S-F A</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p style="text-align: right;">Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Remarks: 	<p style="text-align: right;">Add "Marine Pollutant" to end of proper shipping name if shipping in a bulk container (>119 gallons).</p>
<ul style="list-style-type: none"> · ADR · U.S. Domestic Ground Shipments: · U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: · Emergency Response Guide (ERG) Number: 	<p style="text-align: right;">Same as listed for Standard Shipments above. Same as listed for Standard Shipments above. Not determine</p>

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part A

(Contd. of page 7)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	Not Regulated

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

84852-15-3	4-nonylphenol, branched	≤1%
------------	-------------------------	-----

· TSCA (Toxic Substances Control Act):

25085-99-8	Diglycidyl ether of bisphenol A homopolymer
------------	---

2461-15-6	[[[2-ethylhexyl]oxy]methyl]oxirane
-----------	------------------------------------

64742-94-5	Solvent naphtha (petroleum), heavy arom.
------------	--

13463-67-7	titanium dioxide
------------	------------------

84852-15-3	4-nonylphenol, branched
------------	-------------------------

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

13463-67-7	titanium dioxide
------------	------------------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7	titanium dioxide	A4
------------	------------------	----

· MAK (German Maximum Workplace Concentration)

13463-67-7	titanium dioxide	3A
------------	------------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide
------------	------------------

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part A

(Contd. of page 8)

· Hazard pictograms



GHS07 GHS08

· Signal word Warning

· Hazard statements

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 02/09/2017 / 137

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 2: Reproductive toxicity – Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

1 Identification

- **Product identifier**

- **Trade name:** Sure Bond™ J58 - Part B

- **Article number:** 87-307267B

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Quartz (SiO₂)

3,6-diazaoctanethylenediamin

Solvent naphtha (petroleum), heavy arom.

4-nonylphenol, branched

- **Hazard statements**

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May be fatal if swallowed and enters airways.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 1)

- **Precautionary statements**

Do not breathe dusts or mists.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 1

Reactivity = 2

- **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = 3
FIRE	1	Fire = 1
PHYSICAL HAZARD	2	Reactivity = 2

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

14808-60-7	Quartz (SiO ₂)	25-50%
471-34-1	calcium carbonate	10-25%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	10-25%
100-51-6	Benzyl alcohol	≤ 10%
112-24-3	3,6-diazaoctanethylenediamin	≤ 10%
84852-15-3	4-nonylphenol, branched	≤ 10%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	≤ 2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 2)

- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Immediately call a doctor.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.
Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
471-34-1	calcium carbonate	45 mg/m ³
100-51-6	Benzyl alcohol	30 ppm
112-24-3	3,6-diazaoctanethylenediamin	3 ppm
84852-15-3	4-nonylphenol, branched	3.9 mg/m ³
694-83-7	cyclohex-1,2-ylenediamine	2.1 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	6.5 mg/m ³

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 3)

13463-67-7	titanium dioxide	30 mg/m ³
546-93-0	Magnesite	45 mg/m ³
63148-62-9	Siloxanes and Silicones, di-Me	65 mg/m ³
156-87-6	3-aminopropan-1-ol	8.3 mg/m ³

· PAC-2:

14808-60-7	Quartz (SiO ₂)	33 mg/m ³
471-34-1	calcium carbonate	210 mg/m ³
100-51-6	Benzyl alcohol	52 ppm
112-24-3	3,6-diazaoctanethylenediamin	14 ppm
84852-15-3	4-nonylphenol, branched	43 mg/m ³
694-83-7	cyclohex-1,2-ylenediamine	23 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	72 mg/m ³
13463-67-7	titanium dioxide	330 mg/m ³
546-93-0	Magnesite	260 mg/m ³
63148-62-9	Siloxanes and Silicones, di-Me	720 mg/m ³
156-87-6	3-aminopropan-1-ol	91 mg/m ³

· PAC-3:

14808-60-7	Quartz (SiO ₂)	200 mg/m ³
471-34-1	calcium carbonate	1,300 mg/m ³
100-51-6	Benzyl alcohol	740 ppm
112-24-3	3,6-diazaoctanethylenediamin	83 ppm
84852-15-3	4-nonylphenol, branched	260 mg/m ³
694-83-7	cyclohex-1,2-ylenediamine	140 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	430 mg/m ³
13463-67-7	titanium dioxide	2,000 mg/m ³
546-93-0	Magnesite	1,600 mg/m ³
63148-62-9	Siloxanes and Silicones, di-Me	4,300 mg/m ³
156-87-6	3-aminopropan-1-ol	550 mg/m ³

7 Handling and storage

· Handling:
· Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

· **Information about protection against explosions and fires:** No special measures required.

· Conditions for safe storage, including any incompatibilities
· Storage:

· **Requirements to be met by storerooms and receptacles:** Store in a cool dry location.

· **Information about storage in one common storage facility:**

Store away from incompatible materials.

Store away from foodstuffs.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 4)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

14808-60-7 Quartz (SiO₂)

PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

471-34-1 calcium carbonate

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn

100-51-6 Benzyl alcohol

WEEL	Long-term value: 10 ppm
------	-------------------------

112-24-3 3,6-diazaoctanethylenediamin

WEEL	Long-term value: 6 mg/m ³ , 1 ppm Skin
------	--

1477-55-0 m-phenylenebis(methylamine)

REL	Ceiling limit value: 0.1 mg/m ³ Skin
TLV	Ceiling limit value: 0.1 mg/m ³ Skin

· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 5)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Color: Grey

· Odor: Slight Ammonia

· Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 188 °C (370 °F)

· Flash point: >94 °C (>201 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 335 °C (635 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: 1.3 Vol %

Upper: 13.0 Vol %

· Vapor pressure at 20 °C (68 °F): 0.1 hPa

· Density at 20 °C (68 °F): 1.526 g/cm³ (12.734 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· Solvent content:

Organic solvents: 8.2 %

Solids content: 100.0 %

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 6)

- | | |
|--------------------------------------|--|
| · Other information | No further relevant information available. |
| · Volatile Organic Compounds: | Not determined |

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with acids, alkalis and oxidizing agents.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

112-24-3 3,6-diazaoctanethylenediamin

Oral	LD50	2500 mg/kg (rat)
Dermal	LD50	805 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**
Strong caustic effect.
Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

14808-60-7	Quartz (SiO ₂)	1
13463-67-7	titanium dioxide	2B

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 7)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.
 Danger to drinking water if even small quantities leak into the ground.
 Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
 It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | <p style="margin: 0;">UN1760</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG · IATA | <p style="margin: 0;">Corrosive liquids, n.o.s. (Triethylenetetramine)
 1760 Corrosive liquids, n.o.s. (Triethylenetetramine)
 CORROSIVE LIQUID, N.O.S. (TRIETHYLENETETRAMINE),
 MARINE POLLUTANT
 CORROSIVE LIQUID, N.O.S. (TRIETHYLENETETRAMINE)</p> |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 8)

· **Transport hazard class(es)**· **DOT**

· **Class** 8 Corrosive substances
 · **Label** 8

· **ADR, IATA**

· **Class** 8 Corrosive substances
 · **Label** 8

· **IMDG**

· **Class** 8 Corrosive substances
 · **Label** 8

· **Packing group**· **DOT, ADR, IMDG, IATA** III· **Environmental hazards:**

· **Marine pollutant:** No
 Symbol (fish and tree)

· **Special precautions for user**

· **Danger code (Kemler):** Warning: Corrosive substances
 80
 · **EMS Number:** F-A,S-B
 · **Segregation groups** Alkalis
 · **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**

· **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml
 Same as listed for Standard Shipments above.

· **U.S. Domestic Ground Shipments:**

· **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:** Same as listed for Standard Shipments above.

· **Emergency Response Guide (ERG) Number:** Not determine

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 9)

· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUIDS, N.O.S. (TRIETHYLENETETRAMINE), 8, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

84852-15-3	4-nonylphenol, branched	≤10%
------------	-------------------------	------

· TSCA (Toxic Substances Control Act):

14808-60-7	Quartz (SiO ₂)
471-34-1	calcium carbonate
64742-94-5	Solvent naphtha (petroleum), heavy arom.
100-51-6	Benzyl alcohol
112-24-3	3,6-diazaoctanethylenediamin
84852-15-3	4-nonylphenol, branched
1477-55-0	m-phenylenebis(methylamine)
694-83-7	cyclohex-1,2-ylenediamine
25085-99-8	Diglycidyl ether of bisphenol A homopolymer
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol
13463-67-7	titanium dioxide
124-09-4	hexamethylenediamine
104-15-4	p-toluenesulphonic acid (containing a maximum of 5 % H ₂ SO ₄)
546-93-0	Magnesite
63148-62-9	Siloxanes and Silicones, di-Me
110-60-1	tetramethylenediamine
156-87-6	3-aminopropan-1-ol
15520-10-2	2-methylpentane-1,5-diamine

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

14808-60-7	Quartz (SiO ₂)
13463-67-7	titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 10)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14808-60-7	Quartz (SiO ₂)	A2
13463-67-7	titanium dioxide	A4

· **MAK (German Maximum Workplace Concentration)**

14808-60-7	Quartz (SiO ₂)	1
13463-67-7	titanium dioxide	3A

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)	
13463-67-7	titanium dioxide	

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Quartz (SiO₂)
 3,6-diazaoctanethylenediamin
 Solvent naphtha (petroleum), heavy arom.
 4-nonylphenol, branched

· **Hazard statements**

Causes severe skin burns and eye damage.
 May cause an allergic skin reaction.
 May cause cancer.
 Suspected of damaging fertility or the unborn child.
 May be fatal if swallowed and enters airways.
 Harmful to aquatic life.
 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Do not breathe dusts or mists.
 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/09/2017

Reviewed on 02/09/2017

Trade name: Sure Bond™ J58 - Part B

(Contd. of page 11)

- **National regulations:**
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **Water hazard class:** *Water hazard class 2 (Self-assessment): hazardous for water.*
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** *Environmental, Health & Safety Department*
- **Contact:** *Environmental, Health & Safety Manager*
- **Date of preparation / last revision** *02/09/2017 / 133*
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1A: Carcinogenicity – Category 1A
Repr. 2: Reproductive toxicity – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3