

Green = Compliance

Product	V.O.C. (g/L)	EPA	OTC	LADCO	SCAQMD	CARB	Maryland	Utah**	Canada	Shelf Life (months)
Accelerators		N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	
C-Set	0									12
Q-Set	0									12
Bond Breakers		600	350	350	350/100 ⁴	350	350	350	350	
Sure Lift® J6WB	<100									9
Sure Lift® with Dye J6D	<750	1								24
Sure Lift® J6LVOC	<350									24
Maxi Tilt™ with Dye	<100									9
Cleaners and Strippers		N/R	N/R	N/R	Regulated	Regulated	N/R	N/R	N/R	
Citrus Cleaner J48	<800									24
Zero VOC J49 Cleaner	0									24
Green Bean Clean®	<600									24
Dissolve It	<150									24
Cure & Seals		700	350	350	100	350	350	350	350	
Cure & Seal 309 J18	<200									18
Cure & Seal 1315 J22WB	<350									12
Cure & Seal LV 25% J20UV	<700									24
Cure & Seal 25% J22UV	<700									24
Cure & Seal 30% J23UV	<700									24
Cure & Seal 309 EF	<100									18
Cure & Seal 1315 EF	<100									18
Curing Compounds		350	350	350	100 / 350 ²	350	350	350	350	
Clear Cure VOC J7WB	<100									18
City White Cure J8	<100									12
White Wax Cure J9A	<100									12
White Resin Cure J10W	<350				2					18
Clear Resin Cure J11W	<100									18
Resin Cure with Dye J11WD	<100									18
White Pams Cure	<300				2					18
White Wax Cure CRD300	<100									12
Cure Hard J14	0									
Epoxy Products		N/R	N/R	N/R	N/R	N/R	N/R	350	N/R	
Sure Anchor™ Epoxy J50	0									24
Sure Anchor™ I J51	0									18
All Weather Epoxy J51AW	0									24

SEE NOTES ON PAGE 3

Product	V.O.C. (g/L)	EPA	OTC	LADCO	SCAQMD	CARB	Maryland	Utah**	Canada	Shelf Life (months)
Sure Inject™ J56	0									24
Sure Inject™ J56 SLV	0									24
Sure Seal™ LV/LM	0									24
Sure Bond™ J58	0									24
Sure Bond™ J58 LPL	0									24
Perma Prime™ 3C	0									12
Sure Patch™	0									24
Rebar Spray J62	556*									24
Epoxy Grout J55	0									24
Rapid Resin Repair	0									12
Poxy™-Chock	0									24
Sure Fil™ J52	0									24
Loop Sealant J606	0									24
Evaporation Retardants		N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	
AquaFilm® J74RTU	0									12
Form Releases		450	250	250	100	250	250	250	250	
Clean Strip™ J1 EF	0									12
Clean Strip™ J1A	<250									24
Clean Strip™ J1A Winter Grade	<250									24
Clean Strip™ J100 VOC	<100									24
Clean Strip™ Ultra J3	<250									24
Magic Kote®	<250									24
Clean Strip™ J2	<450									24
Clean Strip™ J2 Winter Grade	<450									24
Pure Pro Zero	0									24
Latex Bonding Agents/Adhesives		N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	
Acrylic Bonding Agent J40	<50									18
PVA Bonding Agent J41	0									12
Level Primer J42	1									12
Level Primer J42RTU	0									12
Liquid Densifiers		N/R	N/R	N/R	N/R	N/R	100	N/R	N/R	
Densifier Concentrate J12	0									12
Densifier J13	0									12
Sure Hard™ Densifier J17	0									12

SEE NOTES ON PAGE 3

Product	V.O.C. (g/L)	EPA	OTC	LADCO	SCAQMD	CARB	Maryland	Utah**	Canada	Shelf Life (months)
PENTRA-HARD® Densifier	<50									36
PENTRA-HARD® Guard	<50									24
PENTRA-HARD® Finish	<50									24
PENTRA-HARD® EDH	<50									12
Sealers		600	400	400	100	400	100	400	400	
Ultra Seal EF	<100									18
AggreGloss™ J25	<700	1								24
AggreGloss™ Satin J25S	<700	1								24
Anti Spall J33	<400									24
Tuf Seal™ J35	<800	1								24
Tuf Seal™ Satin J35S	<800	1								24
Low VOC J25 Sealer	<400									24
Surface Retarders		N/R	N/R	N/R	Regulated	N/R	780	780	N/R	
Top-Cast®					3					24
Face-Off™	<100									24
Top-Cast® SS 100	<100									24
Water Repellants		600	400	400	350	400	350	350	400	
Weather Worker™ 10% J26WB	<100									12
Weather Worker™ 40% J29	<600									24
Weather Worker™ 100% J29A	<250									24

NOTES:

1. Manufacturer pays exceedance fee which allows use of product under EPA regulations.
 2. 350 g/L for Roadways and Bridges ONLY; for all other applications the VOC is 100 g/L.
 3. All grades of Top-Cast are compliant with all Canadian and U.S. VOC regulations for sealers including Federal EPA, OTC, LADCO, SCAQMD and CARB
 4. SCAQMD requires products to conform to lowest VOC for advertised use, so bond breakers fall under cures
- * Aerosol can products are also measured by MIR (maximum incremental activity) or VOC % by weight. J62 has an MIR of 1.22 and a V.O.C. 51.1% by weight
- ** Only seven Utah counties are under these regulations: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber

SCAQMD: In the State of California, all of Orange County, urban portions of Los Angeles, Riverside and San Bernardino Counties

CARB: State of California, other than those under the SCAQMD regulations

OTC: States of CT, DE, MA, ME, NH, NJ, NY, PA, RI, VT, No. VA, District of Columbia

LADCO: States of IL, IN, MI, OH, WI

EPA: All States not governed by the more restrictive aforementioned regulatory agencies

Maryland: Maryland VOC standards changed 1/1/17